### **HD PRO**

Series marked for the installer looking for a high-level camera emphasizing the difference in image quality. The Pro series cameras are suitable for indoor and outdoor applications where professional video surveillance is required.



PROVISION IS

## **DI-380A-28**

#### 20m IR 8MP Fixed Lens Small Dome/Turret Camera

This 4K dome/turret camera presents a stunning 8-megapixel image, equipped with a 2.8mm fixed lens, it is designed for short distance surveillance systems (up to 20m) for both indoor and outdoor scenarios. Featuring 4in1 technology selectable by a protected dipswitch the camera is ideal for Plug & Play over existing analog infrastructure.





















## **MAIN FEATURES**

- DI-380A-28 20m IR 8MP Fixed Lens Small Dome/Turret Camera
- Sensor: 1/2.5" 8MP CMOS Sensor
- Selectable Output: 8MP: 3840×2160 AHD/TVI/CVI 5MP: 2592×1944 AHD/TVI 4MP: 2560×1440 AHD/TVI/CVI CVBS: 700TVL
- Lens: 2.8mm Mega-Pixel Fixed (89.3°)
- True Day&Night-ICR

- 3D-DNR/BLC
- Illumination: 20m (1 High-Power IR LED)
- IP67
- Weight: 485g
- Power: DC12V/340mA



https://provision-isr.com



## **SPECIFICATIONS**

**Lens Mount** 

Video	
Image Sensor	1/2.5" 8MP CMOS Sensor
Image Format	8MP/4MP - 16:9, 5MP - 4:3
Effective Pixels	3864x2202
Scanning System	Progressive
Min. Illumination	Color: 0.01lux@F1.2, AGC ON B/W: 0lux with IR
Day & Night	True Day&Night-ICR
Day & Night Modes	Ext/Auto/Day/Night
Compression	
Resolution	8MP: 3840x2160 AHD/TVI/CVI 5MP: 2592x1944 AHD/TVI 4MP: 2560x1440 AHD/TVI/CVI CVBS: 700TVL
Frame Rate	8MP @ 12/15FPS, 5MP @ 20FPS, 4MP @ 25/30FPS, CVBS @ 25/30FPS
Image	
Image Backlight Compensation	BLC
	BLC ≥52dB (AGC OFF)
Backlight Compensation	
Backlight Compensation S/N Ratio	≥52dB (AGC OFF)
Backlight Compensation  S/N Ratio  Privacy Zone	≥52dB (AGC OFF)
Backlight Compensation  S/N Ratio  Privacy Zone  Noise Reduction	≥52dB (AGC OFF)  no  3D-DNR
Backlight Compensation  S/N Ratio  Privacy Zone  Noise Reduction  Image Enhancement	≥52dB (AGC OFF)  no  3D-DNR
Backlight Compensation  S/N Ratio  Privacy Zone  Noise Reduction  Image Enhancement  On Screen Data	≥52dB (AGC OFF)  no  3D-DNR  BLC
Backlight Compensation  S/N Ratio  Privacy Zone  Noise Reduction  Image Enhancement  On Screen Data  CoC Support	≥52dB (AGC OFF)  no  3D-DNR  BLC  Yes
Backlight Compensation  S/N Ratio  Privacy Zone  Noise Reduction  Image Enhancement  On Screen Data  CoC Support  OSD Menu	≥52dB (AGC OFF)  no  3D-DNR  BLC  Yes

M12 Mount

# **DI-380A-28**



Connectivity	
Audio Connectivity	N/A

Housing	
Illumination	20m (1 High-Power IR LED)
Bracket	3-Axis Bracket
Protection Rate	IP67
Dimensions	Ф97*82.6mm
Weight (gross)	485g
Power	DC12V/340mA
Work Environment	-30°C ~ 50°C , 10% ~ 90% humidity



# **DIMENSIONS**

